








Kangen Water Model Comparison: Product Specifications - Page 1

					
Leveluk Kangen 8 / A26-00	Leveluk SD501 PLATINUM 5-Language	Leveluk SD501 / TYH-401NF	Leveluk SUPER501 / TYH-501	Leveluk JR11 / TYH-201	LEVELUK R / TYH-71
Electrode Plates: 8	Electrode Plates: 7	Electrode Plates: 7	Electrode Plates: 7 and 5	Electrode Plates: 3	Electrode Plates: 3
Languages	Languages	Languages	Languages	Languages	Languages
8 - Display & Audio	5 (English, German, French, Italian, Spanish)	1 (English)	1 (English)	1 (English)	1 (English)
Level Selections	Level Selections	Level Selections	Level Selections	Level Selections	Level Selections
Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 7) Acidic water (approx. pH 5.5-6.5) Strong Acidic water (approx. pH 2.4-2.7) Strong Kangen water (approx. pH 11.0)	Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 7) Acidic water (approx. pH 5.5-6.5) Strong Acidic water (approx. pH 2.4-2.7) Strong Kangen water (approx. pH 11.0)	Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 7) Acidic water (approx. pH 5.5-6.5) Strong Acidic water (approx. pH 2.4-2.7) Strong Kangen water (approx. pH 11.0)	Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 7) Acidic water (approx. pH 5.5-6.5) Strong Acidic water (approx. pH 2.4-2.7) Strong Kangen water (approx. pH 11.3-12.0)	Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 7) Acidic water (approx. pH 5.5-6.5) Strong Acidic water (approx. pH 2.4-2.7) Strong Kangen water (approx. pH 11.0)	Kangen Water® / 3 levels (approx. pH 8.5-9.5) Clean water (pH 8) Acidic water (approx. pH 5.5-6.6)
Water source connection	Water source connection	Water source connection	Water source connection	Water source connection	Water source connection
1-way diverter (TAP/ION) connects to the end of faucet	1-way diverter (TAP/ION) connects to the end of faucet	1-way diverter (TAP/ION) connects to the end of faucet	Regular connection by hose with a nut attached, built-in magnetic valve for water supply	1-way diverter (TAP/ION) connects to the end of faucet	1-way diverter (TAP/ION) connects to the end of faucet
Power Supply	Power Supply	Power Supply	Power Supply	Power Supply	Power Supply
100-240V AC 50/6-Hz 2.6 - 1.1A Worldwide Multi-Voltage Power Supply, with Interchangeable Plug Capability	AC 120V, 60Hz 3.2A (USA) AC220 - 240V 50Hz/60Hz 1.6A (Europe / parts of Asia)	AC 120V, 60Hz 3.2A (USA) AC220 - 240V 50Hz/60Hz 1.6A (Europe / parts of Asia)	AC 120V, 60Hz (diphyletic power unit)	AC 120V, 60Hz 3.2A (USA) AC220 - 240V 50Hz/60Hz 1.6A (Europe / parts of Asia)	AC 120V, 60Hz 3.2A (USA) AC220 - 240V 50Hz/60Hz 1.6A (Europe / parts of Asia)
Power Consumption	Power Consumption	Power Consumption	Power Consumption	Power Consumption	Power Consumption
Energy Saving - Low Input, High Output Approx. 230W (under maximum electrolysis function)	Approx. 230W (under maximum electrolysis function)	Approx. 230W (under maximum electrolysis function)	Approx. 200W	Max. approx. 120W (under maximum electrolysis function)	Approx. 100W (if production is done at Kangen 3 Water pH level)
System	System	System	System	System	System
Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)	Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)	Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)	Continuous Ionized Electrolysis Water Generator System (diphyletic electrolysis vessel)	Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)	Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)



NEWTRITION NEWYOU
FOOD · MIND · BODY

TO BUY OR LEARN MORE:

 (917) 773-8095

 info@newtritionny.com


Kangen Water Model Comparison: Product Specifications - Page 2

					
Production Rate (gallon(s)/minute) Kangen Water®: 1.2-2.0 Acidic water: 0.4-0.7 Strong Acidic water: 0.16-0.3	Production Rate (gallon(s)/minute) Kangen Water®: 0.7-1.1 Strong Acidic water: 0.2-0.3	Production Rate (gallon(s)/minute) Kangen Water®: 0.7-1.1 Strong Acidic water: 0.2-0.3	Production Rate (gallon(s)/minute) Kangen Water®: 1.3-2.1 Flexible right pipe Acidic water: 0.5-0.75 Secondary Hose (White) Acidic Water: 0.4 Flexible left pipe Strong Kangen Water: 0.3 Hose (White)	Production Rate (gallon(s)/minute) Kangen Water®: 0.4-0.7 Strong Acidic water: 0.1-0.2	Production Rate (gallon(s)/minute) Kangen Water®: 0.3-1.2 Clean water: 0-1.2 Acidic water: 0.3-1.0
Electrolysis Capability (continuous use) Approx. 30 min at normal room temperature	Electrolysis Capability (continuous use) Approx. 30 min at normal room temperature	Electrolysis Capability (continuous use) Approx. 30 min at normal room temperature	Electrolysis Capability (continuous use) Approx. 80 min (when salt water tank is filled to capacity). It can be used continuously, if refilled regularly	Electrolysis Capability (continuous use) Approx. 30 min at normal room temperature	Electrolysis Capability (continuous use) Approx. 30 min at normal room temperature
Cell Cleaning Method 10 Second Automatic Cleaning with On-Screen E-Cleaning Instructions	Cell Cleaning Method Auto cleaning system (periodically controlled by microcomputer)	Cell Cleaning Method Auto cleaning system (periodically controlled by microcomputer)	Cell Cleaning Method Auto cleaning - Manual cleaning function	Cell Cleaning Method Auto cleaning system (periodically controlled by microcomputer)	Cell Cleaning Method Auto cleaning system (periodically controlled by microcomputer)
Applicable water quality and pressure Municipally supplied drinking water: dynamic range in 50kpa - 500kpa	Applicable water quality and pressure Municipally supplied drinking water: dynamic range in 100-450kPa	Applicable water quality and pressure Municipally supplied drinking water: dynamic range in 100-450kPa	Applicable water quality and pressure Municipally supplied drinking water 0.05 - 0.5MPa	Applicable water quality and pressure Municipally supplied drinking water: dynamic range in 100-450kPa	Applicable water quality and pressure Municipally supplied drinking water: dynamic range in 100-450kPa
Electrolysis Enhancer Forced dissolving type additive system (One time addition produces approx. 1.0-1.3 gallons of Strong Acidic water.)	Electrolysis Enhancer Forced dissolving type additive system (One time addition produces approx. 1.0-1.3 gallons of Strong Acidic water.)	Electrolysis Enhancer Forced dissolving type additive system (One time addition produces approx. 1.0-1.3 gallons of Strong Acidic water.)	Electrolysis Enhancer Adding method by salt water pump	Electrolysis Enhancer Solution additive pump system	Electrolysis Enhancer N/A
Enhancer Refilling Indicates by voice, buzzer and LCD	Enhancer Refilling Indicates by voice, buzzer and LCD	Enhancer Refilling Indicates by voice, buzzer and LCD	Enhancer Refilling Prior warning by blinking at the time of salt water shortage. Forced stop during a time of salt water shortage	Enhancer Refilling Indicates by buzzer and LCD	Enhancer Refilling N/A
Protector Current Limiter/Voltage Stabilizer/Thermal Protection	Protector Current Limiter/Voltage Stabilizer/Thermal Protection	Protector Current Limiter/Voltage Stabilizer/Thermal Protection	Protector Current limiter - Voltage stabilizer (switching power supply) Fuse 125V 5A Thermal protector (Present temperature 80°C) Short circuit breaker (Sensitivity 15mA) Hot water protector	Protector Current Limiter/Voltage Stabilizer/Thermal Protection	Protector Current Limiter/Voltage Stabilizer/Thermal Protection
Electrode Material Platinum coated Titanium	Electrode Material Platinum coated Titanium	Electrode Material Platinum coated Titanium	Electrode Material Platinum coated Titanium	Electrode Material Platinum coated Titanium	Electrode Material Platinum coated Titanium



NEWTRITION NEWYOU
FOOD · MIND · BODY

TO BUY OR LEARN MORE:

 (917) 773-8095

 info@newtritionny.com